



Airo Swath conditioner

185 & 225



K Two Sales, Fowlers Field Farm, Station Road
Haddenham, Aylesbury, Bucks HP17 8DD
Tel: +44 (0)1844 299 290 Fax: +44 (0)1844 299 390
www.ktwosales.co.uk paul@ktwosales.co.uk

Features of the K Two Airo:

The K Two Airo swath conditioner is manufactured with a heavy duty construction to withstand the high loads imposed by heavy wet grass and straw flowing through the machine at speed.

At the heart of the machine is a rotor with specially developed polyurethane "V" tines which are designed to be safely digested by forage harvesting equipment. The tines lift the swath without touching the ground, thus avoiding soil and stone contamination of the crop. The adjustable conditioner baffle enables the aggressiveness of the conditioning action to be varied to suit crop conditions and customer requirements.

The ability of the Airo to mix and aerate a swath, gives the end user a cheap, fast and useful way of conditioning their crop to their exact requirements enabling quick drying with less effluent runoff once the crop is collected from the field. The adjustable rear baffles of the Airo present the conditioned swath in a good box shaped window, ideal foragers or balers.



Technical Specifications

Model	185		225	
	Metric	Imperial	Metric	Imperial
Working Width	1.85 m	6'	2.28 m	7' 6"
Overall Width	2.60 m	8' 6"	3.00 m	10'
Swath Width	1.20 - 1.85 m	4' - 6'	1.50 - 2.40 m	5' - 7'
Height Adjustment	25 - 150 mm	1" - 6"	25 - 150 mm	1" - 6"
Power Requirement	40 kw	50 hp	50 kw	65 hp
Castor Wheels	600 - 9 (10 ply)			
PTO Speed	540 rpm			
Linkage	CAT II			



Designed to perform



built to last.